J O U R N A L O F

Ceramic Processing Research

Volume 23, Number 2, April 2022

CONTENTS

Research Articles

| The influence of Ca doping on the capacity fading of LiNi _{0.8} Co _{0.1} Mn _{0.1} O ₂ cathode material | Chea-Yun Kang and Seung-Hwan Lee | 109 |
|--|--|-----|
| Composition and ceramic properties of Meskine (Far- North, Cameroon) ball clays: Potential use as raw mate- rials for tiles making | Soureiyatou Fadil-Djenabou, Fuh Calistus Gentry and Paul-Desire Ndjigui | 113 |
| Enhanced efficiency of near-UV LEDs by surface plasmon and magnetic field effects from metal films | Sang-Hyun Hong, Jae-Joon Kim, Byeong-Hyeok Kim, Na-Yeong Kim and Jang-Won Kang | 121 |
| Mechanical properties of geopolymers after immersion | Yootaek Kim and Hakmin Kim | 126 |
| Quenching effect of the exciton emission induced by an electric field in needle-like CdS rods | Hyeoncheol Kim, T.S. Jeong and T. S. Kim | 132 |
| A study on particle morphology and sintering behavior of yttria nano powder according to PVA mixing ratio in polymer solution synthesis route | Dae-Seon Lee, Heon Kong and Sang-Jin Lee | 137 |
| Edge shape effect on the glass strength | Byunghoon Kang, Cheolmin Park, Seungho Kim, Seongtaek Lee and Hoikwan Lee | 145 |
| Effect of MgO-CaO-Al ₂ O ₃ -SiO ₂ glass additive on densi- fication of Al ₂ O ₃ ceramics | Dagyeong Lee, Hyun Seon Hong, Hyeondeok Jeong and Sung-Soo Ryu | 149 |
| Study on the effect of gait cycle improvement with robot assisted rehabilitation | Sun Qiang and Miao Qi | 154 |
| Irradiation time-dependent study of eggshell-derived hydroxyapatite powder synthesized by microwave-assisted wet chemical precipitation method | K.W. Goh, Y.H. Wong, R.S.K. Singh, Hari Chandran, S.K. Wong and K.Y. Sara Lee | 158 |
| EMP shielding of mortar mixed with SiC and graphite | Oh-Seong Park and Hyeong-Kyu Cho | 165 |
| Effect of pyrolysis sintering temperature on the electrical current delivery power of kaolin-carbon composites | Agus Edy Pramono, Sidiq Ruswanto and Nanik Indayaningsih | 171 |
| The effect of ag-epoxy electrodes on the thermal and mechanical properties of multilayer ceramic capacitor | Chang Ho Lee and Jung Rag Yoon | 181 |

| Preparation and characterization of Alumina/Magnesia/ Zirconia/Graphite refractory composites using response surface methodology | Maryam Abolfazli and Mohammad Hossein Paydar | 188 |
|--|--|-----|
| Quenching process effects on the performance of a TiO ₂ photoelectrode for dye-sensitized solar cells | Woon-Yong Park and Ki-Tae Lee | 199 |
| Influence of synthesis parameters on phase evolution and micromorphology of lanthanum hexaaluminate | Xiaoao Li, Jianjiang Xin, Chao Chen, Zhiqiang Du and Haotian Wang | 208 |
| The application of ${\rm TiO_2}$ and noble metal nanomaterials in tele materials | Ruihang Huang and Xiaoming Yang | 213 |
| Microstructural analysis and optimization of welding parameters for AA1100 welded plates | Thirumalai R, Karthick S and Giriraj M | 221 |
| An analysis of ceramic tool condition monitoring for enhanced and secured manufacturing | Thirumalai Ramanathan and Vivekraj M | 228 |
| Optimization of stir casting process parameter using response surface methodology | Senthilkumar KM, Sivakumar A, Rohokale Milind Shivaji, S.K. Tamang and Giriraj M | 233 |
| Effect of La ₂ O ₃ upon optical properties of oxy-fluoride glasses | Taewan Ha and Seunggu Kang | 237 |